



ACCESSORIES

Isoflect POWER TAPE

Aluminium tape for sealing and ensuring the continuity of Reflectiva membranes

Self-adhesive aluminium tape for sealing joints and overlaps in Reflectiva membranes. It ensures the continuity of the radiant barrier and the vapour barrier over the entire surface — without it, the reflective assembly is not complete.

TECHNICAL CHARACTERISTICS

Width	10 cm
Roll length	50 m
Service temperature range	−60 ... +140 °C
Required for Floor Pro	One roll for each roll of Floor Pro (40 m ²)
Required for the Renofit package	One roll per 40 m ²

NOTICE — incomplete data sheet: the tape thickness, the adhesive type and weight, the adhesion values, the application temperature range and the UV resistance are not declared. To be completed from the supplier's data sheet before publication.

FIELDS OF USE

Sealing of joints and overlaps in Reflectiva Gold, Silver, Bronze, Multistrat and Floor Pro; perimeter junctions, service passages and penetrations.

PACKAGING AND STORAGE

In the original packaging, in covered spaces, protected from moisture and direct sunlight.

INSTALLATION

Apply to a clean, dry, dust-free surface, pressing firmly along the entire length of the joint. Membrane overlaps are covered entirely, so that the vapour barrier is continuous.

S.C. ISO FLECT INSULATION S.R.L.

CIF RO30340616 · Reg. com. J2012000359286
Șos. Caragea Vodă nr. 89A, Domnești, sat Țegheș, jud. Ilfov, Romania

Warehouse and deliveries

ELI Park 3, secțiunea S10, Str. Speranței 101, Buftea, Ilfov, Romania
+40 21 780 7585 · WhatsApp +40 790 644 051 · contact@isoflect.ro

The declared values come from the Isoflect Insulation product documentation and the related test reports. They refer to the product, not to the assembly in which it is installed; system performance is established through a hygrothermal calculation for each individual case. The manufacturer reserves the right to change specifications without prior notice — always check the revision in force. Revision 4 · 13.09.2026